

STOCK FWD CLASS RULES

1. All drivers must wear full faced helmet, full fire suit, and shoes (gloves recommended)
2. All cars must have 4 or 5 point racing harness
3. All cars must have functioning window net on drivers window
4. All cars must have some type of screen and or at least three 1/4" bars on drivers side windshield
5. All cars must have working brakes on driven wheels minimum.
6. All cars must have hole in hood or no inner fenders in case of fire
7. All Cars must have 12"x12" three sided number sign on roof. Make sure it is secured down and must be visible at all times on the track (White background with dark numbers)
8. All Cars must be cleaned out—no trash, junk, or loose debris
9. All cars must have steel firewall and any holes covered with steel.
10. All doors must be welded and or chained shut
11. All hoods/trunks must be pinned shut (no nut/bolt combinations or chains)
12. All wheel weights must be removed
13. Aluminum racing seat required and must be securely mounted with a minimum of two 3/8" bolts on bottom and one 3/8" bolt on the back.
14. All glass, trim, and plastic bumper covers must be removed prior to arriving at the track
15. Gas tanks/fuel cells must be securely fastened and protected in car with no leaks
16. If fuel line runs through cockpit the line needs to be inside a secured steel conduit that runs from firewall to back decking.
17. Any transmission coolers must be secure with no leaks and hoses should be covered for safety.
18. No profanity or anything inappropriate allowed on cars—this is a family event. Track officials will remove or cover up at drivers expense.
19. Battery must be secured tightly in a battery box and covered. Passenger floorboard is recommended
20. Closed shoulder radial, passenger, and racing tires only. No mud and snows or all terrain tires. No tire alterations
21. No beadlock rims. Standard car rims only.
22. Front and rear bumper mandatory. OEM style bumpers off any car may be welded on front and rear of car.. No tubes, bars, or any other metal can be used to support or brace the bumper other than attaching it to the car. Must not be wider than the body of the car.
23. Factory body or 18 gauge max thickness with no overlaying.
24. Drivers door only may have 1 bar across it not exceeding 4 inches past either door seam and not be any taller than 8 inches. It may be welded or bolted No grader blades
25. No welding done on car other than bumpers, doors and cage.
26. Roll bar mandatory. 4 post with drivers door bar(s) recommended
27. 4 or 6 cylinder engines only